

## VIBRATORY HAMMERS EXCAVATOR MOUNTED

	230B	328B	428B	528B
Eccentric moment	2.2	3.2	4.6	5.6
Max. frequency	3000	2800	2800	2800
Max. centrifugal force	220	275	344	481
Max. line pull capacity	120	120	120	120
Max. hydr. power	53/72	65/88	98/133	98/133
Max. oil flow	90	110	170	170
Dynamic weight (**)	720	740	900	910
Total weight (**)	1080	1090	1280	1290
Max. amplitude (**)	6.1	8.6	10.2	12.3
L x W x H (**)	1128 x 520 x 980	1128 x 520 x 980	1128 x 646 x 980	1128 x 646 x 980
Recommended clamp	40TU	40TU	60TU	60TU

	625B	823B	1223B
Eccentric moment	6.0	8.0	11.5
Max. frequency	2500	2300	2300
Max. centrifugal force	411	465	670
Max. line pull capacity	120	120	180
Max. hydr. power	117/159	108/147	190/258
Max. oil flow	201	185	326
Dynamic weight (**)	910	940	1890
Total weight (**)	1300	1310	2380
Max. amplitude (**)	13.2	17.0	12.2
L x W x H (**)	1128 x 646 x 980	1128 x 646 x 980	1540 x 435 x 1170
Recommended clamp	60TU	60TU	100TU



\*\* ) INCLUDING CLAMP